

SECTION 1: Identification

1.1. Identification

Product form	: Mixture
Product name	: DOT 3 Brake fluid
Product code	: 58132
Other means of identification	: 58132-58134

1.2. Recommended use and restrictions on use

Use of the substance/mixture	: Brake fluid
------------------------------	---------------

1.3. Supplier

Bardahl Pro
1400 NW 52nd Street
Seattle, 98107 - USA
T 206-783-4851 - F 206-784-3219
www.bardahl.com
Contact: Jackie Leung

1.4. Emergency telephone number

Emergency number	: 800-424-9300
------------------	----------------

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids, Category 4	Combustible liquid
Acute toxicity (oral), Category 4	Harmful if swallowed.
Skin corrosion/irritation, Category 2	Causes skin irritation.
Serious eye damage/eye irritation, Category 1	Causes serious eye damage.
Specific target organ toxicity — Repeated exposure, Category 2	May cause damage to organs (kidneys, liver, central nervous system) through prolonged or repeated exposure (oral).

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: Combustible liquid
Harmful if swallowed.
Causes skin irritation.
Causes serious eye damage.
May cause damage to organs (kidneys, liver, central nervous system) through prolonged or repeated exposure (oral).

Precautionary statements (GHS US)

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear eye protection, protective clothing, protective gloves.
If swallowed: Call a POISON CENTER if you feel unwell.
If on skin: Wash with plenty of water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Get medical advice/attention if you feel unwell.
Specific treatment (see supplemental first aid instruction on this label).
Rinse mouth.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use media other than water to extinguish.

DOT 3 Brake fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Store in a well-ventilated place. Keep cool.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Triethylene glycol monobutyl ether	(CAS-No.) 143-22-6	>= 50	Eye Dam. 1, H318
2-(2-Butoxyethoxy) Ethanol	(CAS-No.) 112-34-5	< 20	Eye Irrit. 2, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material.

DOT 3 Brake fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DOT 3 Brake fluid	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	10 ppm 2-(2-butoxyethoxy)ethanol
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ diethylene glycol
Triethylene glycol monobutyl ether (143-22-6)	
No additional information available	
2-(2-Butoxyethoxy) Ethanol (112-34-5)	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Liquid.

Colour : Colourless to light yellow

Odour : Ether-like odour

Odour threshold : No data available

pH : 7 - 11

Melting point : < -50 °C Not applicable

Freezing point : No data available

Boiling point : > 210 °C

Flash point : > 93 °C CC per ASTM D 93

DOT 3 Brake fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: 0.07 mm Hg @ 20C, estimated.
Relative vapour density at 20 °C	: > 5 Air = 1
Relative density	: 1.05 @ 15.6C
Solubility	: Miscible with water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 1.8 mm ² /s @ 100C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

DOT 3 Brake fluid	
LD50 oral rat	> 5000 mg/kg Triethylene glycol monobutyl ether (143-22-6)
LD50 dermal rabbit	3480 mg/kg Triethylene glycol monobutyl ether (143-22-6)
ATE US (oral)	500 mg/kg bodyweight
ATE US (dermal)	3480 mg/kg bodyweight

Skin corrosion/irritation	: Causes skin irritation. pH: 7 - 11
Serious eye damage/irritation	: Causes serious eye damage. pH: 7 - 11
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

DOT 3 Brake fluid	
IARC group	4 - Probably not carcinogenic to humans, 3 - Not classifiable

Reproductive toxicity : Not classified

DOT 3 Brake fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (kidneys, liver, central nervous system) through prolonged or repeated exposure (oral).
Aspiration hazard	: Not classified
Viscosity, kinematic	: 1.8 mm ² /s @ 100C
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
-------------------	---

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

DOT 3 Brake fluid	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

DOT 3 Brake fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CANADA

EU-Regulations

National regulations


No additional information available

15.3. US State regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date	: 01/03/2020
NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection	: B B - Safety glasses, Gloves

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.