



TECH REPORT



The Original Bardahl USA

# XTG SYNTHETIC GEAR OIL 75W-90

*Specifications: API GL-5*

Product No(s): 75590

## Product Description

**XTG SYNTHETIC GEAR OIL 75W-90** Synthetic Limited Slip Gear Oil is a synthetic multipurpose gear lubricant designed specifically for high performance automotive applications. Required for many European, Domestic and Asian automobiles, this lubricant is well suited for areas where low temperature start-ups may be encountered. Formulated for use in passenger cars and truck axles with hypoid gear set operating in extreme temperatures or under severe driving conditions. Ideal for limited slip drain and fill or top-off application.

## Advantages & Uses

- API Service GL-5
- Meets SAE J2360 requirements
- High performance Domestic and Foreign automobiles
- Suitable for both, limited-slip and non limited-slip applications

## Features

- Allows start-up at extremely low temperatures
- EP additives for wear protection
- Good rust protection
- Compatible with other automotive gear oils
- Improves fuel economy
- Multi-grade provides year round use
- Non-Foaming.
- Limited-Slip
- Protects hypoid gears from wear and scuffing



## Typical Specifications

TEST	ASTM	Result
Gravity, °API	D-287	32.1
Flash Point, °F	D-92	400
Viscosity: cSt @ 100 °C	D-445	16.0
Viscosity Index	D-2270	120
Brookfield Viscosity, cP @-40C	D-2983	100,000
Color	D-1500	3.0

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY